

TECHNICAL SHEET: S-31400

BLACK DRY GUIDE COAT SPRAY

DESCRIPTION AND FIELDS OF APPLICATION

It is a black spray product that can be applied on the repair area before sanding and that once sanded shows all the imperfections of the surface being worked on.

It is a fast and clean product that does not need to dry.

It also has an advantage cost-wise because no preparation of cleaning or tools is required.

VOC 690 g/l – 2004/42/EC – IIB (e) (840)

TECHNICAL DATA

Composition:	Nitrosynthetic
Specific weight:	0,8 kg/l at 20°C
Colour:	Black
Safety data:	Refer to the safety sheet
Storage:	12 months, under appropriate storage conditions





CAUTIONS

- After use, turn can upside and empty the valve.
- If the diffuser jams, replace it with a new one.
- Store in a cool, ventilated place, avoiding direct exposure to sunlight.
- Store between +5°C and +30°C.

TECHNICAL SHEET: S-31400

BLACK DRY GUIDE COAT SPRAY

INSTRUCTIONS FOR USE - APPLICATION

	<p>Shake the aerosol before use for 1 minute after hearing the sound of steel mixing balls. Protect the areas that do not need to be painted.</p>
	<p>30 cm</p>
	<p>1 coat</p>
	<p>5 min</p>

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.
