

LIGHT PUTTY

Universal light polyester putty

DESCRIPTION AND FIELDS OF APPLICATION


Polyester flexible putty with a low specific weight. Very easy to spread, exceptional sanding, elasticity and impact resistance. Very low permeability to humidity, excellent resistance to atmospheric agents and strong adhesive power. It is particularly suitable every time the lightness is an important topic.

The VOC of this product ready-to-use is 25 g/l - category limit as defined by EC Directive 2004/42/EC IIB (b) (250).

TECHNICAL DATA

Composition:	Unsaturated polyester resins and special fillers
Specific weight:	1,20 ± 0,1 kg/l
Available colours:	Beige
Safety data:	Refer to the safety sheet
Storage:	12 months, under appropriate storage conditions

SURFACE PREPARATION






	<ul style="list-style-type: none"> • Zinc-plated sheet, aluminium and its alloys, iron, steel plate, plastics. • Original paints or aged topcoat finishes. • Clean well the surface to be treated with 6005 Degreaser. Make sure it is dry and free from silicone, wax, grease and any extraneous material. • On base coats or enamel top coats, sand and clean the surface before applying the putty.
---	--

CAUTIONS

<ul style="list-style-type: none"> • Mix well the adhesive with 2-3 % paste hardener. Do not exceed with the hardener to avoid risk of staining during painting operations. • Do not use the product at temperatures below 5°C. • Keep in a cool, dry place.

LIGHT PUTTY
Universal light polyester putty

PROCESSING

	2-3% paste hardener Pot-life = 5' at 20°C
	Application by putty knife
	25' at 20°C
	5' at 80 cm. TMAX 80°C
	P100-P240

TOOLS CLEANING

With nitro or washing thinner

FURTHER STEPS

1K Primer
 Spray Filler
 2K Acrylic Primer

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.