

TECHNICAL SHEET: S-83400

GLOSS BLACK TOPCOAT SPRAY

DESCRIPTION AND FIELDS OF APPLICATION

Premium acrylic enamel.

An extreme high content of pigments and specific additives provide excellent opacity, high film-thickness, low tendency for runs and good adhesion direct on steel, galvanised and aluminium.

It can be applied either for spot repairs or refinishing parts.

VOC 692 g/l – 2004/42/EC – IIB (e) (840)

TECHNICAL DATA

Composition:	Thermoplastic acrylic resin
Specific weight:	0,8 kg/l a 20°C
Colour:	Satin black
Safety data:	Refer to the safety sheet
Storage:	12 months, under appropriate storage conditions








CAUTIONS

- Do not apply the product on connected equipment.
- After use, reverse the cylinder and empty the valve.
- If the diffuser jams, replace it with a new one.
- Store in a cool, ventilated place, avoiding direct exposure to sunlight.
- Store between +5°C and +30°C.

TECHNICAL SHEET: S-83400

GLOSS BLACK TOPCOAT SPRAY

INSTRUCTIONS FOR USE - APPLICATION

	<p>Shake the aerosol before use at least for 2 minutes after hearing the steel mixing balls move. Carry out test spray. Check the colour.</p>
	<p>20-25 cm</p>
	<p>2-3 coats Dry film thickness: 15-20 µ/coat</p>
	<p>5 min</p>
	<p>20°C: 10-15 min</p>
	<p>20°C: 60 min</p>
	<p>in order to increase the degree of gloss and to enhance the fuel resistance, recoat it after approx. 15 min flash-off time (20°C) with 1K clear coat.</p>

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.
