

TECHNICAL SHEET: S-20400

1K GLOSS CLEAR COAT SPRAY

DESCRIPTION AND FIELDS OF APPLICATION

A fast drying , high gloss, U.V. resistant clear coat, applicable for all standard base coats.

Easy to polish, very good flow, ideally suited for spot repairs.

It can be applied either for spot repairs or can be used for refinishing complete parts.

VOC 661 g/l – 2004/42/EC – IIB (e) (840)

TECHNICAL DATA

Composition:	Thermoplastic acrylic resin
Specific weight:	0,8 kg/l at 20°C
Colour:	Transparent
Safety data:	Refer to the safety sheet
Storage:	12 months, under appropriate storage conditions








CAUTIONS

- Not suitable for recoating water-based paints.
- Do not apply the product on connected equipment.
- After use, reverse the cylinder and empty the valve.
- If the diffuser jams, replace it with a new one.
- Store in a cool, ventilated place, avoiding direct exposure to sunlight.
- Store between +5°C and +30°C.

TECHNICAL SHEET: S-20400

1K GLOSS CLEAR COAT SPRAY

INSTRUCTIONS FOR USE - APPLICATION

	<p>Shake the aerosol before use for 2 minutes after hearing the sound of steel mixing balls. Protect the areas that do not need to be painted.</p>
	<p>20-25 cm</p>
	<p>2-3 coats: 50 μ Dry film thickness: 15-20 μ/coat</p>
	<p>2-3 min</p>
	<p>20°C: 5-10 min</p>
	<p>20°C: 10-20 min</p>
	<p>20°C: 24h 60°C: 40 min</p>

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.
