

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : KMK 8220 2K TOPCOAT JET BLACK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Paint

Recommended restrictions on use : For use in industrial installations or professional treatment only.

1.3 Details of the supplier of the safety data sheet

Company : Kimakem srl
Via Don G. Fortuna 82
36050 Monteviale-Vicenza
Italia

Telephone : +39 0444 1220020

E-mail address of person responsible for the SDS : info@kimakem.com

1.4 Emergency telephone number

+39 0444 1220020 (Mon to Fri - 8:30 to 17:30)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure, Category 2 H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects.

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P260 Do not breathe spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

n-butyl acetate
xylene (mixture of isomers)
Solvent naphtha (petroleum), light arom.
Hydrocarbons, C10, aromatics, <1% naphthalene

Additional Labelling

EUH208 Contains Reaction product of pentamethyl-piperidyl sebacate. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

KMK 8220 2K TOPCOAT JET BLACK

 Version
1.1

 Revision Date:
26.01.2018

SECTION 3: Composition/information on ingredients
3.2 Mixtures

Chemical nature : Paint

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 20 - < 30
xylene (mixture of isomers)	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0 649-356-00-4	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10
Hydrocarbons, C10, aromatics, <1% naphthalene	Not Assigned 918-811-1 01-2119463583-34	STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 01-2119475112-47	Acute Tox. 4; H302 Acute Tox. 4; H312	>= 1 - < 10
Reaction product of pentamethyl-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1
naphthalene	91-20-3 202-049-5	Acute Tox. 4; H302 Carc. 2; H351	>= 0,0025 - < 0,025

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

	601-052-00-2 01-2119561346-37	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
Substances with a workplace exposure limit :			
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:
Headache
Vertigo
Fatigue
Weakness
Skin contact may provoke the following symptoms:
Redness
Pain
Ingestion may provoke the following symptoms:
Abdominal pain
Nausea

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

Vomiting
Diarrhoea

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For subsequent waste disposal, follow the recommendations in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : <** Phrase language not available: [EN] CUST - Z99.00000000038 **>

Storage period : 12 Months

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the use of this product do not exist particular recommendations apart from that already indicated.

KMK 8220 2K TOPCOAT JET BLACK

 Version
1.1

 Revision Date:
26.01.2018

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	VLA-ED	150 ppm 724 mg/m ³	ES VLA
		VLA-EC	200 ppm 965 mg/m ³	ES VLA
xylene (mixture of isomers)	1330-20-7	VLA-ED	50 ppm 221 mg/m ³	ES VLA
Further information	Skin, Chemical agent for which a specific Biological Limit Value exists in this document., Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
		VLA-EC	100 ppm 442 mg/m ³	ES VLA
Further information	Skin, Chemical agent for which a specific Biological Limit Value exists in this document., Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
		TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		VLA-EC	100 ppm 550 mg/m ³	ES VLA
Further information	Skin, Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

		VLA-ED	50 ppm 275 mg/m ³	ES VLA
Further information	Skin, Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		VLA-ED	100 ppm 441 mg/m ³	ES VLA
Further information	Skin, Chemical agent for which a specific Biological Limit Value exists in this document., Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
		VLA-EC	200 ppm 884 mg/m ³	ES VLA
Further information	Skin, Chemical agent for which a specific Biological Limit Value exists in this document., Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 333 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		VLA-ED	20 ppm 133 mg/m ³	ES VLA
Further information	Skin, Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
		VLA-EC	50 ppm 333 mg/m ³	ES VLA
Further information	Skin, Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

	shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
naphthalene	91-20-3	TWA	10 ppm 50 mg/m ³	91/322/EEC
Further information	Indicative			
		VLA-ED	10 ppm 53 mg/m ³	ES VLA
Further information	Skin, Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
		VLA-EC	15 ppm 80 mg/m ³	ES VLA
Further information	Skin, Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	480 mg/m ³
xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
Low boiling point naphtha - unspecified	Workers	Inhalation	Long-term systemic effects	608 mg/m ³
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
Hydrocarbons, C10, aromatics, <1% naphthalene	Workers	Skin contact	Long-term systemic effects	12,5 mg/m ³
	Workers	Inhalation	Long-term systemic effects	151 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	7,5 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	7,5 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	32 mg/m ³
ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
2-butoxyethyl acetate	Workers	Inhalation	Long-term systemic effects	133 mg/m ³

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

naphthalene	Workers	Skin contact	Long-term systemic effects	3,57 mg/m3
	Workers	Inhalation	Long-term systemic effects	25 mg/m3
	Workers	Inhalation	Long-term local effects	25 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
naphthalene	Soil	0,0533 mg/l
	Fresh water	0,0024 mg/l
	Marine water	0,0024 mg/l
	Fresh water sediment	0,0672 mg/l
	Marine sediment	0,0672 mg/l
	Sewage treatment plant	2,9 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Material : Solvent-resistant gloves

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection

: In the case of vapour formation use a respirator with an approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : viscous liquid

Colour : yellow

Odour : characteristic

pH : Not applicable

Melting point/range : not determined

Boiling point/boiling range : not determined

Flash point : 28 °C
Method: ISO 1523, closed cup
Setaflash

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapour pressure	:	not determined
Density	:	1,023 g/cm ³ (20 °C) Method: ISO 2811-1
Solubility(ies) Water solubility	:	immiscible
Viscosity Viscosity, dynamic	:	494 mPa.s (20 °C) Method: ISO 2555
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No data available

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

- Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method
- Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

n-butyl acetate:

- Acute oral toxicity : LD50 Oral (Rat): 10.768 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): 23,4 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 (Rabbit): 17.600 mg/kg
Method: OECD Test Guideline 402

xylene (mixture of isomers):

- Acute oral toxicity : LD50 Oral (Rat): 4.300 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): 22,08 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
- Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Converted acute toxicity point estimate

Solvent naphtha (petroleum), light arom.:

- Acute oral toxicity : LD50 Oral (Rat): 3.592 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

Acute dermal toxicity : LD50 (Rabbit): 3.160 mg/kg
Method: OECD Test Guideline 402

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3.500 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 17,4 mg/l
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 15.400 mg/kg
Method: OECD Test Guideline 402

2-butoxyethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 1.880 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Converted acute toxicity point estimate

Reaction product of pentamethyl-piperidyl sebacate:

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

naphthalene:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Converted acute toxicity point estimate

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 8.532 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 35,7 mg/l
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

Acute dermal toxicity : LD50 (Rat): 5.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Result: Skin irritation

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Germ cell mutagenicity-
Assessment : Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Carcinogenicity -
Assessment : Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Reproductive toxicity -
Assessment : Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Product:

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Fish): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): 32 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae | : | EC50 (Algae): 675 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |

xylene (mixture of isomers):

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Fish): 14 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): 16 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae | : | EC50 (Algae): > 10 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |

Solvent naphtha (petroleum), light arom.:

- | | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Fish): 9,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): 3,2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

Toxicity to algae : EC50 (Algae): 2,9 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Hydrocarbons, C10, aromatics, <1% naphthalene:

Toxicity to fish : LC50 (Fish): 1 - 10 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Crustaceans): 1 - 10 mg/l

Toxicity to algae : EC50 (Algae): 1 - 10 mg/l

ethylbenzene:

Toxicity to fish : LC50 (Fish): 12 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1,8 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 33 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

2-butoxyethyl acetate:

Toxicity to fish : LC50 (Fish): 28 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 37 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 1.570 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Reaction product of pentamethyl-piperidyl sebacate:

Toxicity to fish : LC50 (Fish): 0,9 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 20 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

Toxicity to algae : EC50 (Algae): 1,68 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

naphthalene:

Toxicity to fish : LC50 (Fish): 0,1 - 1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 0,1 - 1 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 0,1 - 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Fish): 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 408 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

12.2 Persistence and degradability

Components:

Hydrocarbons, C10, aromatics, <1% naphthalene:

Biodegradability : Biodegradation: 50 %
Exposure time: 28 d

naphthalene:

Biodegradability : Concentration: 100 mg/l
Biodegradation: 2 %
Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

naphthalene:

Bioaccumulation : Bioconcentration factor (BCF): 168

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

Partition coefficient: n-
octanol/water : log Pow: 3,3

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADR : 1263
IMDG : UN 1263
IATA (Cargo) : UN 1263

14.2 UN proper shipping name

ADR : PAINT
IMDG : PAINT

KMK 8220 2K TOPCOAT JET BLACK

Version 1.1 Revision Date: 26.01.2018

IATA (Cargo) : Paint

14.3 Transport hazard class(es)

ADR : 3

IMDG : 3

IATA (Cargo) : 3

14.4 Packing group

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Exemption: Not subject to ADR according to section 2.2.3.1.5, Transport in accordance with 2.3.2.5 of the IMDG Code.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c	FLAMMABLE LIQUIDS	Quantity 1 5.000 t	Quantity 2 50.000 t
-----	-------------------	-----------------------	------------------------

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t
----	---	---------	----------

Other regulations:

The product is classified and labelled in accordance with EC directives or respective national laws.

15.2 Chemical safety assessment

The supplier has not carried out evaluation of chemical safety.

SECTION 16: Other information

Full text of H-Statements

EUH066	:	Repeated exposure may cause skin dryness or cracking.
H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
------------	---	----------------

KMK 8220 2K TOPCOAT JET BLACK

Version

1.1

Revision Date:

26.01.2018

Aquatic Acute	:	Acute aquatic toxicity
Aquatic Chronic	:	Chronic aquatic toxicity
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
91/322/EEC	:	Europe. Commission Directive 91/322/EEC on establishing indicative limit values
ES VLA	:	Spain. Environmental Limits for exposure to Chemical agents - Table 1: Occupational Exposure Values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
91/322/EEC / TWA	:	Limit Value - eight hours
ES VLA / VLA-ED	:	Environmental Daily Limit Value
ES VLA / VLA-EC	:	Environmental Short Term Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

KMK 8220 2K TOPCOAT JET BLACK

Version
1.1

Revision Date:
26.01.2018

Further information

Sources of key data used to compile the Safety Data Sheet : <http://echa.europa.eu>, <http://eur-lex.europa.eu>

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Calculation method
Based on product data or assessment
Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ES / EN