

TECHNICAL SHEET: S-30400

1K ADHESION PROMOTER SPRAY

DESCRIPTION AND FIELDS OF APPLICATION

Single component adhesive promoter with anti-corrosive power.
It stands out because of its excellent adhesion on various surfaces such as plastic, galvanized metals, aluminium, steel, among others.
Very fast drying.
We recommend it be used as an adhesive promoter. Refinish with a 1K or 2K primer for a better result.

VOC 701 g/l – 2004/42/EC – IIB (e) (840)

TECHNICAL DATA

Composition:	Resin mixture
Specific weight:	0,8 kg/l a 20°C
Colour:	Grey
Safety data:	Refer to the safety sheet
Storage:	12 months, under appropriate storage conditions


CAUTIONS

- Do not apply the product on connected equipment.
- After use, reverse the cylinder and empty the valve.
- If the diffuser jams, replace it with a new one.
- Store in a cool, ventilated place, avoiding direct exposure to sunlight.
- Store between +10°C and +25°C.

TECHNICAL SHEET: S-30400

1K ADHESION PROMOTER SPRAY

INSTRUCTIONS FOR USE - APPLICATION

	<p>Shake the aerosol before use for 1 minute after hearing the sound of steel mixing balls. Protect the areas that do not need to be painted. Carry out test spray. Check the colour.</p>
	<p>20-25 cm</p>
	<p>1-2 coats Dry film thickness: 7-15 μ/coat We recommend applying thin and even coats</p>
	<p>20 min</p>
	<p>20°C: aprox 12 min</p>
	<p>Refinish with a 1k o 2k primer 20°C: 15 min - 2h</p>

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.
