

# **TECHNICAL SHEET: 8230**

## 2K TOPCOAT BRILLANT SILVER MET 2K glossy topcoat. Color: metalized gray

### DESCRIPTION AND FIELDS OF APPLICATION

2K high gloss polyurethane-acrylic topcoat. Color: metalized gray. High brightness and durable. Great quality of the finish and good weather resistance. Ideal for finishes in commercial vehicles, agricultural machinery and construction projects where the final finish is an important requirement.

In accordance with the category limits imposed by Directive 2004/42 / EC IIA (i) (500).

### **TECHNICAL DATA**

Composition:	Polyurethane acrylic resins and pigments
Specific weight:	1,0 kg/l (20ºC)
Color:	Metalized gray
Safety data:	Refer to the safety sheet

### SURFACE PREPARATION

Clean well the surface to be treated with 6005 Degreaser, before and after sanding. Sanding: Old paints, with P360/400 Primers, optional with P320

### CAUTIONS

*	Store the product in a ventilated place far from direct exposure to sunlight.
*	Keep between +5 <sup>o</sup> C and +30 <sup>o</sup> C.



# **TECHNICAL SHEET: 8230**

## 2K TOPCOAT BRILLANT SILVER MET 2K glossy topcoat. Color: metalized gray

### PROCESSING

л . в . с	2:1 with hardener: 4025-4125-4225-4325 +20% thinner: 5005-5105
S	20" - 23″ DIN 4mm at 20ºC Pot-life: 8h
	1,3 - 1,5 mm 2-3 bar 2 = 40-50 microns
<u>}</u>	10'-15' of evaporation according to temperature
	5h at 20ºC 30' at 60ºC

### **TOOLS CLEANING**

Clean with a cleaning thinner before the product hardens.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.

Kimakem srl Via Don G. Fortuna 82 36050 Monteviale – Vicenza (Italy) info@kimakem.com www.kmk-refinish.com