

BASECOAT JET BLACK
Double layer black paint

DESCRIPTION AND FIELDS OF APPLICATION


Double layer paint, composed of polyester resins 1K. Color: black.
It has a satin finish and it is fast-drying.
Excellent coverage and easy to apply.
It always needs a clearcoat, preferably 2K.
The product must be applied in installations that comply with Directive 1999/13/CE.

In accordance with the category limits imposed by Directive 2004/42 / EC IIA (i) (500).

TECHNICAL DATA

Composition:	1K polyester resins and pigments
Specific weight:	0,9 kg/l (20°C)
Color:	Black
Safety data:	Refer to the safety sheet

SURFACE PREPARATION






	Clean well the surface to be treated with 6005 Degreaser, before and after sanding. Sanding: old paints, with P360/400
---	---

CAUTIONS

* Recommended to be used in ventilated spray booth at 20°C.
* Store the product in a ventilated place far from direct exposure to sunlight.
* Keep between +5°C and +30°C.

BASECOAT JET BLACK
Double layer black paint

PROCESSING

	60% thinner 5005-5105
	17" - 20" DIN 4mm at 20°C
	1,3 - 1,5 mm 3-4 bar 2 = 20-30 microns
	20' at 20°C
	Apply a 2K clearcoat 2001-2505-2605-2705-2805

TOOLS CLEANING

Clean with a cleaning thinner before the product hardens.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.