

TECHNICAL SHEET: 8220

2K TOPCOAT JET BLACK

2K glossy topcoat. Color: black

DESCRIPTION AND FIELDS OF APPLICATION


2K high gloss polyurethane-acrylic topcoat. Color: black
High brightness and durable.
Great quality of the finish and good weather resistance.
Ideal for finishes in commercial vehicles, agricultural machinery and construction projects where the final finish is an important requirement.

In accordance with the category limits imposed by Directive 2004/42 / EC IIA (i) (500).

TECHNICAL DATA

Composition:	Polyurethane acrylic resins and pigments
Specific weight:	1,0 kg/l (20°C)
Color:	Black
Safety data:	Refer to the safety sheet

SURFACE PREPARATION

	Clean well the surface to be treated with 6005 Degreaser, before and after sanding. Sanding: Old paints, with P360/400 Primers, optional with P320
---	--

CAUTIONS






- * Store the product in a ventilated place far from direct exposure to sunlight.
- * Keep between +5°C and +30°C.

TECHNICAL SHEET: 8220

2K TOPCOAT JET BLACK

2K glossy topcoat. Color: black

PROCESSING

	2:1 with hardener: 4025-4125-4225-4325 +20% thinner: 5005-5105
	20" - 23" DIN 4mm at 20°C Pot-life: 8h
	1,3 - 1,5 mm 2-3 bar 2 = 40-50 microns
	10'-15' of evaporation according to temperature
	5h at 20°C 30' at 60°C

TOOLS CLEANING

Clean with a cleaning thinner before the product hardens.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.