

**KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST**



**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier:** KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST

**Other means of identification:**

**UFI:** Q9G4-RPTP-D00Y-UTFP

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses (Professional users): Varnish

Relevant uses (Industrial user): Varnish

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

Kimakem srl

Via Don G. Fortuna 82

36050 Monteviale - Vicenza - Italia

Phone: +39 0444 1220020

info@kimakem.com

<https://www.kmk-refinish.com>

**1.4 Emergency telephone number:** +39 0444 1220020 (Monday to Friday 8:30 -17:30 GMT +1:00)

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

**Warning**



**Hazard statements:**

H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

H336 - May cause drowsiness or dizziness.

H373 - May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

**Supplementary information:**

- CONTINUED ON NEXT PAGE -

**KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST**



**SECTION 2: HAZARDS IDENTIFICATION (continued)**

EUH208: Contains Hidroxyphenyl-Benzotriazole derivate, Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

**Substances that contribute to the classification**

Xylene; N-butyl acetate; Hydrocarbons, C9, aromatics; 2-methoxy-1-methylethyl acetate

**UFI:** Q9G4-RPTP-D00Y-UTFP

**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\***

**3.1 Substance:**

Not relevant

**3.2 Mixture:**

**Chemical description:** Mixture composed of additives and resins in solvents

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(1)</sup></b> Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified  <b>10 - &lt;25 %</b>
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	<b>N-butyl acetate<sup>(1)</sup></b> Regulation 1272/2008	ATP CLP00 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	  <b>10 - &lt;25 %</b>
CAS: 64742-95-6 EC: Not relevant Index: Not relevant REACH: Not relevant	<b>Hydrocarbons, C9, aromatics<sup>(1)</sup></b> Regulation 1272/2008	Self-classified Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	  <b>5 - &lt;10 %</b>
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	<b>Ethylbenzene<sup>(1)</sup></b> Regulation 1272/2008	Self-classified Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	  <b>5 - &lt;10 %</b>
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	<b>2-methoxy-1-methylethyl acetate<sup>(1)</sup></b> Regulation 1272/2008	Self-classified Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	  <b>1 - &lt;2,5 %</b>
CAS: 112-07-2 EC: 203-933-3 Index: 607-038-00-2 REACH: 01-2119475112-47-XXXX	<b>2-butoxyethyl acetate<sup>(1)</sup></b> Regulation 1272/2008	ATP CLP00 Acute Tox. 4: H312+H332 - Warning	  <b>1 - &lt;2,5 %</b>
CAS: 104810-48-2 EC: 600-603-4 Index: Not relevant REACH: Not relevant	<b>Hidroxyphenyl-Benzotriazole derivate<sup>(1)</sup></b> Regulation 1272/2008	Self-classified Aquatic Chronic 2: H411; Skin Sens. 1: H317 - Warning	  <b>0,3 - &lt;0,5 %</b>
CAS: 108-01-0 EC: 203-542-8 Index: 603-047-00-0 REACH: 01-2119492298-24-XXXX	<b>2-dimethylaminoethanol<sup>(1)</sup></b> Regulation 1272/2008	Self-classified Acute Tox. 3: H331; Acute Tox. 4: H302+H312; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Corr. 1B: H314; STOT SE 3: H335 - Danger	  <b>0,1 - &lt;0,3 %</b>
CAS: 41556-26-7 EC: 255-437-1 Index: Not relevant REACH: Not relevant	<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate<sup>(1)</sup></b> Regulation 1272/2008	Self-classified Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317 - Warning	  <b>0,1 - &lt;0,3 %</b>

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>(2)</sup> Substance with a Union workplace exposure limit

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST



### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\* (continued)

Identification	Chemical name/Classification		Concentration
CAS: 82919-37-7 EC: 280-060-4 Index: Not relevant REACH: Not relevant	<b>Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate<sup>(1)</sup></b>		Self-classified
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317 - Warning	! 
CAS: 80-62-6 EC: 201-297-1 Index: 607-035-00-6 REACH: 01-2119452498-28-XXXX	<b>Methyl methacrylate<sup>(2)</sup></b>		ATP CLP00
	Regulation 1272/2008	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	 

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:

Identification	Specific concentration limit
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	% (w/w) >=5: STOT SE 3 - H335

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	Not relevant	
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation vapour	17 mg/L	Rat
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	Not relevant	
	LD50 dermal	Not relevant	
	LC50 inhalation vapour	17,2 mg/L	Rat
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	LD50 oral	Not relevant	
	LD50 dermal	1580 mg/kg	Rat
	LC50 inhalation vapour	11 mg/L	
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	LD50 oral	1182 mg/kg	Rat
	LD50 dermal	1220 mg/kg	Rabbit
	LC50 inhalation vapour	5,97 mg/L	Rat

\*\* Changes with regards to the previous version

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

##### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

##### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

##### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

##### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

- CONTINUED ON NEXT PAGE -



## SECTION 4: FIRST AID MEASURES (continued)

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media:

#### Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

#### Unsuitable extinguishing media:

Water jet

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

### 6.4 Reference to other sections:

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -



## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

#### A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

#### B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

#### C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

#### D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

#### A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

#### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>
Methyl methacrylate	IOELV (8h)	50 ppm	
CAS: 80-62-6 EC: 201-297-1	IOELV (STEL)	100 ppm	
Xylene <sup>(1)</sup>	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate <sup>(1)</sup>	IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>
Ethylbenzene <sup>(1)</sup>	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>
2-butoxyethyl acetate <sup>(1)</sup>	IOELV (8h)	20 ppm	133 mg/m <sup>3</sup>
CAS: 112-07-2 EC: 203-933-3	IOELV (STEL)	50 ppm	333 mg/m <sup>3</sup>

<sup>(1)</sup> Skin

### DNEL (Workers):

**KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification	Short exposure		Long exposure	
	Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Not relevant	Not relevant	Not relevant
	Dermal	11 mg/kg	Not relevant	11 mg/kg
	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>
Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: Not relevant	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	25 mg/kg
	Inhalation	Not relevant	Not relevant	150 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	180 mg/kg
	Inhalation	Not relevant	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	796 mg/kg
	Inhalation	Not relevant	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	Oral	Not relevant	Not relevant	Not relevant
	Dermal	120 mg/kg	Not relevant	169 mg/kg
	Inhalation	Not relevant	333 mg/m <sup>3</sup>	133 mg/m <sup>3</sup>
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	Oral	Not relevant	Not relevant	Not relevant
	Dermal	1,2 mg/kg	Not relevant	0,25 mg/kg
	Inhalation	5,28 mg/m <sup>3</sup>	13,53 mg/m <sup>3</sup>	1,76 mg/m <sup>3</sup>
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 82919-37-7 EC: 280-060-4	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0,5 mg/kg
	Inhalation	Not relevant	Not relevant	0,68 mg/m <sup>3</sup>
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	13,67 mg/kg
	Inhalation	Not relevant	416 mg/m <sup>3</sup>	348,4 mg/m <sup>3</sup>
<b>DNEL (General population):</b>				
Identification	Short exposure		Long exposure	
	Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	2 mg/kg	Not relevant
	Dermal	6 mg/kg	6 mg/kg	Not relevant
	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>
Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: Not relevant	Oral	Not relevant	11 mg/kg	Not relevant
	Dermal	Not relevant	11 mg/kg	Not relevant
	Inhalation	Not relevant	32 mg/m <sup>3</sup>	Not relevant
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	1,6 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	15 mg/m <sup>3</sup>	Not relevant
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Not relevant	36 mg/kg	Not relevant
	Dermal	Not relevant	320 mg/kg	Not relevant
	Inhalation	Not relevant	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	Oral	36 mg/kg	8,6 mg/kg	Not relevant
	Dermal	72 mg/kg	102 mg/kg	Not relevant
	Inhalation	Not relevant	200 mg/m <sup>3</sup>	80 mg/m <sup>3</sup>
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	Oral	Not relevant	0,126 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,438 mg/m <sup>3</sup>	Not relevant

- CONTINUED ON NEXT PAGE -

**KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 82919-37-7 EC: 280-060-4	Oral	Not relevant	Not relevant	0,05 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,25 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,17 mg/m³	Not relevant
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Oral	Not relevant	Not relevant	8,2 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	8,2 mg/kg	Not relevant
	Inhalation	Not relevant	208 mg/m³	74,3 mg/m³	104 mg/m³

**PNEC:**

Identification					
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L	
	Soil	2,31 mg/kg	Marine water	0,327 mg/L	
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	12,46 mg/kg	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L	
	Soil	0,09 mg/kg	Marine water	0,018 mg/L	
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,098 mg/kg	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L	
	Soil	2,68 mg/kg	Marine water	0,01 mg/L	
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg	
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L	
	Soil	0,29 mg/kg	Marine water	0,064 mg/L	
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,329 mg/kg	
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	STP	90 mg/L	Fresh water	0,304 mg/L	
	Soil	0,415 mg/kg	Marine water	0,03 mg/L	
	Intermittent	0,56 mg/L	Sediment (Fresh water)	2,03 mg/kg	
	Oral	0,06 g/kg	Sediment (Marine water)	0,203 mg/kg	
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	STP	10 mg/L	Fresh water	0,066 mg/L	
	Soil	0,01 mg/kg	Marine water	0,004 mg/L	
	Intermittent	0,661 mg/L	Sediment (Fresh water)	0,246 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,015 mg/kg	
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 82919-37-7 EC: 280-060-4	STP	1 mg/L	Fresh water	0,002 mg/L	
	Soil	0,21 mg/kg	Marine water	0 mg/L	
	Intermittent	0,009 mg/L	Sediment (Fresh water)	1,05 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,11 mg/kg	
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	STP	10 mg/L	Fresh water	0,94 mg/L	
	Soil	1,48 mg/kg	Marine water	0,094 mg/L	
	Intermittent	0,94 mg/L	Sediment (Fresh water)	10,2 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,102 mg/kg	

**8.2 Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

- CONTINUED ON NEXT PAGE -

**KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Filter mask for gases and vapours (Filter type: A)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Antistatic and fireproof protective clothing		EN 1149-1:2007 EN 1149-2:1998 EN 1149-3:2004 UNE-EN ISO 18526-1 al 4:2020 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2022	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011		DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	51,1 % weight
V.O.C. density at 20 °C:	510 kg/m³ (510 g/L)
Average carbon number:	7,37
Average molecular weight:	114,44 g/mol

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### **Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not relevant *

#### **Volatility:**

Boiling point at atmospheric pressure:	138 °C
Vapour pressure at 20 °C:	844 Pa
Vapour pressure at 50 °C:	4347,52 Pa (4,35 kPa)
Evaporation rate at 20 °C:	Not relevant *

#### **Product description:**

Density at 20 °C:	998 kg/m <sup>3</sup>
Relative density at 20 °C:	0,998
Dynamic viscosity at 20 °C:	474 cP
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	>20,5 mm <sup>2</sup> /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Immiscible
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

#### **Flammability:**

Flash Point:	28 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	245 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *

#### **Particle characteristics:**

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

### 9.2 Other information:

#### **Information with regard to physical hazard classes:**

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

#### **Other safety characteristics:**

Surface tension at 20 °C:	Not relevant *
---------------------------	----------------

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

## KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST



### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index: Not relevant \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION \*\*

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

##### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

##### B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

##### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

##### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST**



**SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)**

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

**F- Specific target organ toxicity (STOT) - single exposure:**

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. Organs affected: All gross lesions and masses.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation vapour	23,4 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation vapour	17 mg/L	Rat
Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: Not relevant	LD50 oral	>3492 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rat
	LC50 inhalation vapour	30 mg/L (4 h)	Rat
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation vapour	17,2 mg/L	Rat
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	LD50 oral	2820 mg/kg	Rat
	LD50 dermal	1580 mg/kg	Rat
	LC50 inhalation vapour	11 mg/L	
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	LD50 oral	1182 mg/kg	Rat
	LD50 dermal	1220 mg/kg	Rabbit
	LC50 inhalation vapour	5,97 mg/L	Rat
Hidroxyphenyl-Benzotriazole derivate CAS: 104810-48-2 EC: 600-603-4	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate CAS: 41556-26-7 EC: 255-437-1	LD50 oral	2615 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 82919-37-7 EC: 280-060-4	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation dust	>5 mg/L	

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST



### SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

Identification		Acute toxicity		Genus
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	LD50 oral	>2000 mg/kg		
	LD50 dermal	>2000 mg/kg		
	LC50 inhalation vapour	>20 mg/L		

#### Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	7890,49 mg/kg (Calculation method)	0 %
Dermal	5878,19 mg/kg (Calculation method)	0 %
LC50 inhalation vapour	62,57 mg/L (4 h) (Calculation method)	0 %

#### 11.2 Information on other hazards:

##### Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

##### Other information

Not relevant

\*\* Changes with regards to the previous version

### SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

#### 12.1 Toxicity:

##### Acute toxicity:

Identification		Concentration		Species	Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	>10 - 100 mg/L (96 h)			Fish
	EC50	>10 - 100 mg/L (48 h)			Crustacean
	EC50	>10 - 100 mg/L (72 h)			Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Not relevant			
	EC50	Not relevant			
	EC50	675 mg/L (72 h)		Scenedesmus subspicatus	Algae
Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: Not relevant	LC50	>1 - 10 mg/L (96 h)			Fish
	EC50	>1 - 10 mg/L (48 h)			Crustacean
	EC50	>1 - 10 mg/L (72 h)			Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42,3 mg/L (96 h)		Pimephales promelas	Fish
	EC50	75 mg/L (48 h)		Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)		Chlorella vulgaris	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)		Pimephales promelas	Fish
	EC50	481 mg/L (48 h)		Daphnia sp.	Crustacean
	EC50	Not relevant			
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	LC50	80 mg/L (48 h)		Leuciscus idus	Fish
	EC50	37 mg/L (48 h)		Daphnia magna	Crustacean
	EC50	500 mg/L (72 h)		Scenedesmus subspicatus	Algae
Hidroxyphenyl-Benzotriazole derivate CAS: 104810-48-2 EC: 600-603-4	LC50	>1 - 10 mg/L (96 h)			Fish
	EC50	>1 - 10 mg/L (48 h)			Crustacean
	EC50	>1 - 10 mg/L (72 h)			Algae
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	LC50	146 mg/L (96 h)		Leuciscus idus	Fish
	EC50	98,4 mg/L (48 h)		Daphnia magna	Crustacean
	EC50	35 mg/L (72 h)		Scenedesmus subspicatus	Algae
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate CAS: 41556-26-7 EC: 255-437-1	LC50	0,97 mg/L (96 h)		Lepomis macrochirus	Fish
	EC50	20 mg/L (24 h)		Daphnia magna	Crustacean
	EC50	Not relevant			

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST**



**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Concentration		Species	Genus
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 82919-37-7 EC: 280-060-4	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	LC50	191 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	69 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	170 mg/L (96 h)	Selenastrum capricornutum	Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	Not relevant		
	NOEC	23,2 mg/L	Daphnia magna	Crustacean
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC	Not relevant		
	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 82919-37-7 EC: 280-060-4	NOEC	Not relevant		
	NOEC	1 mg/L	Daphnia magna	Crustacean
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	NOEC	9,4 mg/L	Danio rerio	Fish
	NOEC	37 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	5 days
	BOD5/COD	Not relevant	% Biodegradable	84 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	90 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Not relevant	Concentration	785 mg/L
	COD	Not relevant	Period	8 days
	BOD5/COD	Not relevant	% Biodegradable	100 %
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	BOD5	Not relevant	Concentration	30 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	77,3 %
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	60,5 %
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	94,3 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2,77
	Potential	Low

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST



### SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

Identification		Bioaccumulation potential	
N-butyl acetate		BCF	4
CAS: 123-86-4		Pow Log	1.78
EC: 204-658-1		Potential	Low
Ethylbenzene		BCF	1
CAS: 100-41-4		Pow Log	3.15
EC: 202-849-4		Potential	Low
2-methoxy-1-methylethyl acetate		BCF	1
CAS: 108-65-6		Pow Log	0.43
EC: 203-603-9		Potential	Low
2-butoxyethyl acetate		BCF	3
CAS: 112-07-2		Pow Log	1.51
EC: 203-933-3		Potential	Low
2-dimethylaminoethanol		BCF	3
CAS: 108-01-0		Pow Log	-0.73
EC: 203-542-8		Potential	Low
Methyl methacrylate		BCF	7
CAS: 80-62-6		Pow Log	1.38
EC: 201-297-1		Potential	Low

#### 12.4 Mobility in soil:

Identification		Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol	
	Conclusion	Moderate	Dry soil	Yes	
	Surface tension	Not relevant	Moist soil	Yes	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Not relevant	Henry	Not relevant	
	Conclusion	Not relevant	Dry soil	Not relevant	
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Not relevant	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m <sup>3</sup> /mol	
	Conclusion	Moderate	Dry soil	Yes	
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes	
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	Koc	Not relevant	Henry	5,532E-1 Pa·m <sup>3</sup> /mol	
	Conclusion	Not relevant	Dry soil	Not relevant	
	Surface tension	Not relevant	Moist soil	Yes	
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	Koc	1.2	Henry	1,8E-4 Pa·m <sup>3</sup> /mol	
	Conclusion	Very High	Dry soil	Not relevant	
	Surface tension	3,111E-2 N/m (25 °C)	Moist soil	Not relevant	
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Koc	Not relevant	Henry	Not relevant	
	Conclusion	Not relevant	Dry soil	Not relevant	
	Surface tension	2,551E-2 N/m (25 °C)	Moist soil	Not relevant	

#### 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

#### 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

#### 12.7 Other adverse effects:

Not described

\*\* Changes with regards to the previous version

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

- CONTINUED ON NEXT PAGE -



## SECTION 13: DISPOSAL CONSIDERATIONS (continued)

### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



**14.1 UN number or ID number:** UN1263  
**14.2 UN proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
 Special regulations: 163, 367, 650  
 Tunnel restriction code: D/E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

### Transport of dangerous goods by sea:

With regard to IMDG 41-22:



**14.1 UN number or ID number:** UN1263  
**14.2 UN proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** III  
**14.5 Marine pollutant:** No  
**14.6 Special precautions for user**  
 Special regulations: 223, 955, 163, 367  
 EmS Codes: F-E, S-E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
 Segregation group: Not relevant  
**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

### Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

- CONTINUED ON NEXT PAGE -

## KMK 2501R HS 2K 2\_1 ANTI-SCRAT. FAST



### SECTION 14: TRANSPORT INFORMATION (continued)



**14.1 UN number or ID number:** UN1263  
**14.2 UN proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
 Physico-Chemical properties: see section 9  
**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

### SECTION 15: REGULATORY INFORMATION \*\*

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

#### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

#### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

\*\* Changes with regards to the previous version

### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

- CONTINUED ON NEXT PAGE -



## SECTION 16: OTHER INFORMATION (continued)

### COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances

Hidroxyphenyl-Benzotriazole derivate (104810-48-2)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Substances contained in EUH208:

- New declared substances

Hidroxyphenyl-Benzotriazole derivate (104810-48-2)

REGULATORY INFORMATION (SECTION 15):

- Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....)

**Texts of the legislative phrases mentioned in section 2:**

H336: May cause drowsiness or dizziness.

H335: May cause respiratory irritation.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 3: H331 - Toxic if inhaled.

Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin.

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

STOT SE 3: Calculation method

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

Aquatic Chronic 3: Calculation method

STOT RE 2: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

- CONTINUED ON NEXT PAGE -



## SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -