

TECHNICAL SHEET: S-91400

GREY BUMPER SPRAY Grey textured plastic paint

DESCRIPTION AND FIELDS OF APPLICATION

Flexible textured coating for plastics and bumpers. Ideal for restoring the original incision after a repair.

Its spray format makes it particularly advantageous for small jobs, as it requires neither preparation nor cleaning of the equipment.

- Multifunctional.
- Pre-varnished primer or polyester putty.
- Structure and appearance similar to the original plastic bumpers.
- Good adhesion to most plastic supports.

VOC 655 g/l – 2004/42/EC – IIB (e) (840)

TECHNICAL DATA

Composition:	Nitrocombined ligand
Specific weight:	0,8 kg/l at 20°C
Colour:	Anthracite
Safety data:	Refer to the safety sheet
Storage:	12 months, under appropriate storage conditions








CAUTIONS

- Do not apply the product on connected equipment.
- After use, reverse the cylinder and empty the valve.
- If the diffuser jams, replace it with a new one.
- Store in a cool, ventilated place, avoiding direct exposure to sunlight.
- Store between +5°C and +30°C.

TECHNICAL SHEET: S-91400

GREY BUMPER SPRAY Grey textured plastic paint

INSTRUCTIONS FOR USE - APPLICATION

	<p>Shake the spray well before use, about a minute after hearing the mixer noise.</p>
	<p>10-25 cm</p>
	<p>2-3 coats: 15 μ/coat Apply thin layers to obtain a superior quality finish and an optimal drying time.</p>
	<p>5 min</p>
	<p>20°C 2 coats: 3 min 3 coats: 4 min</p>
	<p>20°C 2 coats: 3 min 3 coats: 6 min</p>
	<p>20°C 2 coats: 10 min 3 coats: 15 min</p>

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.