

TECHNICAL SHEET: S-33400

DARK GREY PRIMER FILLER SPRAY

DESCRIPTION AND FIELDS OF APPLICATION

1K isolating primer filler for bodywork repair.
Express drying.
Ideal for quick repairs and for small surfaces that need to be finished quickly.
Excellent adherence on the different materials used in vehicle bodywork (putties, electro-galvanized sheets, primers and old paints).
It can be overpainted with any kind of bodywork enamel.

VOC 692 g/l – 2004/42/EC – IIB (e) (840)

TECHNICAL DATA

Composition:	Nitrosynthetic
Specific weight:	0,9 kg/l at 20°C
Colour:	Dark grey
Safety data:	Refer to the safety sheet
Storage:	12 months, under appropriate storage conditions








CAUTIONS

- Do not apply the product on connected equipment.
- After use, reverse the cylinder and empty the valve.
- If the diffuser jams, replace it with a new one.
- Store in a cool, ventilated place, avoiding direct exposure to sunlight.
- Store between +5°C and +30°C.

TECHNICAL SHEET: S-33400

DARK GREY PRIMER FILLER SPRAY

INSTRUCTIONS FOR USE - APPLICATION

	<p>Shake the aerosol before use for 2-3 minutes after hearing the sound of steel mixing balls. Protect the areas that do not need to be painted.</p>
	<p>15-20 cm</p>
	<p>2-3 coats Dry film thickness: 20-25 μ/coat</p>
	<p>5 min</p>
	<p>10°C: 10 min 20°C: 5 min 30°C: 3 min</p>
	<p>10°C: 25 min 20°C: 15 min 30°C: 10 min</p>
	<p>10°C: 25-60 min 20°C: 15-30 min 30°C: 10-20 min</p>

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained.
